


**CRYPTON BRAKE TESTER
QUICK REFERENCE GUIDE**

Applies to CBT6500, CBT7500, CVBT7600, CVBT8500, EB30-2R/P Upgrade

IMPORTANT: BEFORE OPERATING THIS EQUIPMENT ENSURE YOU HAVE READ AND UNDERSTOOD THE OPERATORS MANUAL.

Test Procedure

Reset System



then



CENTRALISE



once vehicle central press stop



LEFT SIDE



apply brakes to lock, or press stop

STORE VALUE



RIGHT SIDE



apply brakes to lock, or press stop

STORE VALUE



Bind, Ovality and Imbalance (one continuous sequence)

BIND

DO NOT APPLY BRAKES.

Press



wait for display to show measured
bind or three dashes (below 20Kg)
Proceed to Ovality

OVALITY

APPLY BRAKES TO APPROX 500Kg

Press



Display shows **to**. Wait approx 6
seconds for display to change to **BAL**

IMBALANCE

APPLY BRAKES TO APPROX 90% OF MAXIMUM EFFORT AND
SLOWLY RELEASE

Press Stop




Bind, Ovality and imbalance
sequence is complete

STORE VALUES



DRIVE OUT

Use test to start rollers



CHANGE AXLE



Display shows A2 or A3 etc

PARK BRAKE

PRESS



LEFT SIDE



apply brakes to lock, or press stop

STORE VALUE



RIGHT SIDE



apply brakes to lock, or press stop

STORE VALUE



**APPLIED PARK BRAKE TEST
(ONLY WHERE APPLICABLE)
FOLLOW ABOVE KEY SEQUENCE.
IF ROLLERS DO NOT STOP AUTOMATICALLY AFTER 3
SECONDS PRESS STOP.**

SECONDARY BRAKE

PRESS



LEFT SIDE



apply brakes to lock, or press stop

STORE VALUE



RIGHT SIDE



apply brakes to lock, or press stop

STORE VALUE

